

SuperLead

3300H

二维码防爆扫描枪

2D Area Explosion-proof Imager



高性价比
Cost-effective

品质高
High Quality



- 多国语言条码信息直传
- 自感应读取条码
- 精准的红光瞄准器
- 高速、全方位的一维、二维码影像读取
- 手机屏幕条码读取
- 符合人体工程学设计

- Multiple Language Barcode Message Transfer
- Object Auto Sense
- Accurate Aimer
- Read all Mainstream 1D/2D Barcodes
- Cellphone Sscreen Barcode Reading
- Extremely Easy to Use

Physical Characteristics	
尺寸Dimensions:	170mm x 95mm x 70mm
重量Weight:	126g
电压Voltage:	5VDC
电流Current:	350mA
Performance Characteristics	
传感器像素Image(Pixels):	640 pixels(H) x 480 pixel(V)
光源Light Source:	illumination: 3500K
视场角Field of View:	36°(H) x 25°(V)
旋转倾斜偏转Roll/Pitch/Yaw:	360°,±65°,±60°
打印对比度Print Contrast:	25% minimum reflective difference
运动容差Motion Tolerances:	up to 25 in. (63.5cm) per second
接口支持Interfaces Supported:	USB,RS232
Symbology Decode Capability	
一维条码/1-D	UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar Interleaved 2 of 5, etc
二维条码/2-D	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, etc.
User Environment	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
抗震性Shock Specifications	Designed to withstand 1.5m(5') drops
环境光免疫Ambient Light Lmmunity:	100,000 Lux
Decode Ranges	
Code 39 (5 mil)	30mm - 150mm
100%upca (13 mil)	50mm - 380mm
Code 39 (17.8 mil)	20mm - 230mm
1D Minimal resolution	4mil
Performance may be impacted by bar code quality and environmental conditions	
RoHS COMPLIANT  CE  	